

NETYS PL

600 and 800 VA

a multi-socket UPS for easier connections



Technology

> Offline



Technical data

NetYS PL		
Sn	600 VA	800 VA
Pn	360 VA	480 VA
Power (surge)	1200 VA	
Input/output	1/1	
INPUT		
Rated voltage	230 V	
Voltage tolerance	180 ÷ 270 V	
Rated frequency	50/60 Hz with automatic selection	
Mains connection	Cable with plug	
OUTPUT		
Rated voltage	230 V ±10%	
Rated frequency	50/60 Hz ±1%	
Wave form	Step wave	
Protection	Overload, deep discharge and short circuit	
Sockets	4 sockets for UPS and surge protection, 2 sockets for surge protection	
Socket standard	British, French or German	
BATTERIES		
Type	Sealed lead-acid maintenance free - expected life 3/5 years	
Back-up time ⁽¹⁾	15 min	20 min
COMMUNICATION		
Interfaces	USB	
Local communication software	Local View	
UPS CABINET		
Dimensions W x D x H	220 x 220 x 123 mm	
Weight	3.6 kg	4.1 kg
STANDARDS		
Safety	EN 62040-1	
EMC	EN 62040-2	

(1) PC + 17" LCD monitor.

The solution for

- PC: LCD or CRT monitors, scanners, printers, etc.
- Cash registers
- Interactive terminals

Standard electrical features

- USB port to charge mobile devices

Standard communication features

- **LOCAL VIEW:** ideal UPS monitoring and shutdown point-to-point solution for Windows®, Linux and Mac OS X operating systems.